




主机参数：

最高转速	6500r/min	整机噪音	<58dB
最大离心力	6082xg	电 源	AC22050HZ15A
最大容量	4 × 00ml	整机功率	650W
转速精度	±10rpm	重 量	38KG
定时范围	1s-99h59min59s	外型尺寸	570x440x350mm(LxWxH)

适配转子：

NO.1 角转子  12×15ml 转速：6500r/min 离心力：6082xg 备注：PP/PC管	适配器  12x5/2ml	NO.2 水平转子  钢叉转子 转速：5000r/min 离心力：4752xg	不锈钢摆架  4×100ml	不锈钢摆架  4×50ml	适配器  4×15/10/ml
NO.3 水平转子  钢叉转子 转速：4200r/min 离心力：3353xg	不锈钢摆架  4×2×100ml	不锈钢摆架  4×2×50ml	适配器  8×15/10ml	不锈钢摆架  4×8×15ml	挂具  4×12×5/2ml
NO.4 水平转子  72×5/2ml 转速：4200r/min 离心力：3061xg	NO.5 水平吊篮  4×400ml 转速：4200r/min 离心力：3379xg	适配器  4×16×5/2ml	适配器  4×9×15/10ml	适配器  4×4×50ml	适配器  4×1×100ml
NO.6 水平吊篮  4×250ml 转速：4200r/min 离心力：3361xg	适配器  4×11×5/2ml	适配器  4×7×15/10ml	适配器  4×1×50ml	适配器  4×1×100ml	适配器  4×13×1.5ml
NO.7 酶标转子  2×2×96孔 转速：4200r/min 离心力：3057xg 备注：适用于PCR板，96孔板、微孔板、深孔板等。	适配器  2×32×1.5ml				